



INSPECTION & MAINTENANCE PROCEDURE FOR HARNESSSES

Component	Aspect Examined	Condition			
		N/A	OK	Minor Defect	Major Defect
Webbing	Cuts or tears or Mildew				
	Abrasion damage especially where there is contact with hardware				
	Excessive stretching				
	Heat deformation, and damage from corrosives or chemicals				
	Localised Discolouration, Localised hardening				
	Deterioration due to UV or other factors				
Buckles Adjusters	Distortion or other physical damage				
	Cracks				
	Corrosion				
D-Rings	Examine for excess movement at its attachment point				
	Cracks				
	Distortion or other damage				
	Loss of cross-section due to wear				
	Corrosion				
Sewing	Broken, cut or worn threads				
	Damage or weakening of threads				
	Damage due to heat, corrosives or chemicals				
	Deterioration due to UV or other factors				
	Unauthorised repairs				
Labelling	Serial Number Legible				
	Product Label Inspection legible				
	Product Description Legible				

Maintenance & Cleaning

- Luke warm water with dish soap can be considered the best & safest method of cleaning, without any adverse effects on the metal components. Rinse parts in luke-warm water after cleaning.
- After necessary cleaning & drying, store the equipment in a dry, dark cool position, away from chemicals, corrosives, high humidity, sharp objects, U.V radiations, salt environment, or any other possible causes of damage.
- Do not store the equipment wet.

NOTES:

Date of Inspection:

Name of Inspector:

Inspectors Signature: